

# maestro38

Compose your setting in tune with one of our most popular premium range carpets

heavy contract

38 colourways





Auburn Falls



Azure Fusion



Beige




Blue Diamond



Bracken Salts



Brooklyn Nights



Deep Blue



Delhi Bazaar



Dublin Bay



Dusky Pink




Earth Glaze



Emerald Orchestra



Celestial Blue




Charcoal



Claret



Cocoa Blush



Coral



Dark Green



Gold



Hot Paprika




Indian Ivy



Night Jewel



Nutshell



Red



Royal Regetta    Sapphire    Silver    Steel    Sunflower    Sycamore    Teal



Turquoise    Twilight    Velvet Truffle    Volcanic Splash    Woodland Fern    Gunmetal    Terracotta

Suitable for offices, retail, schools, colleges and leisure









Heavy contract


10 year warranty


Available in plain cutpile tile and broadloom options


38 colourways

Up to 55% recycled content in the bitumen backing

-  **Style**  
1/10" gauge Tufted Cut Pile Tile
-  **Yarn Construction**  
100% Antron Nylon
-  **Pile Yarn Weight**  
1050 gsm
-  **Pile Height**  
5mm
-  **Pile Density**  
181,102 tufts per m2
-  **Total Weight**  
4955 gsm (Tile)
-  **Total Thickness**  
8mm (Tile)
-  **Backing**  
Bitumen Backed
-  **Dimensions**  
50cm x 50cm
-  **Wear Classification**  
Heavy Contract

 **Anti-static**  
< 2kV body voltage  
Suitable for use with computers

 **Colour Fastness**  
To Light (ISO105 – BO2) > 5  
To Water (ISO 105 - E01) > 4  
To Rubbing (ISO 105 - X12) > 4

 **Flammability**  
Flammability (BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790  
Low radius of Char  
(Hot Metal Nut Test) CE Flam rating - Bfl-s1

 **Castor Chair Test**  
BS EN 985  
r value 2.8

continuous use

**INSTALLATION**

Sub floors should be clean, dry and flat and prepared in accordance with BS5325. Timber floors should be covered with plywood or other appropriate sheet materials. For tiles use F Ball tackifier F41 or Laybond 79. Tiles may be laid tessellated or broadloom. Tiles should be allowed to condition for a minimum of 24 hours at the expected temperature and humidity prevailing when the building is in use. Further installation information is available from the Paragon Sales Office.


**COLOUR**

For technical reasons, as with all textile materials, it may not be possible to colour match from different batches. Orders requiring colour match should be placed at the same time. Production may therefore show variations to the sample card.

**MAINTENANCE**

It is recommended that a maintenance schedule be initiated from the date of installation to achieve maximum life expectancy of the product. Regular vacuum cleaning with a twin motored upright vacuum cleaner is essential. All spillages and stains should be attended to immediately. For detailed information, please consult the Paragon cleaning and maintenance guide. It is imperative that all internal carpets are well protected from outside soiling and moisture by the use of barrier matting such as MatWorks, also available from Paragon.





paragon

Farfield Park  
Manvers  
Wath-upon-Dearne  
Rotherham, S63 5DB.

T. +44 (0) 1709 763 839  
F. +44 (0) 1709 763 813  
E. [sales@paragon-carpets.co.uk](mailto:sales@paragon-carpets.co.uk)  
W. [www.paragon-carpets.co.uk](http://www.paragon-carpets.co.uk)