

NBS SPECIFICATION; Workspace Solid BRE A + Rated

M50 RUBBER/PLASTICS/CORK/LINO/CARPET/TILING/SHEETING CARPET
TILING.

MANUFACTURER: -PARAGON, A Division of National Floor Coverings Ltd. Farfield
Park, Manvers, Wath upon Dear, Rotherham, S63 5DB, tel 0845 601 0431

Workspace Solid CARPET TILES

A tufted loop pile carpet tile manufactured from 100% solution dyed, 1/10" gauge
Available in 8 colourways and carries a Class 4 Heavy Contract Rating
The 6mm thick tile is available in 500 x 500mm . Size options are available with
minimum quantities.

B.S. 14001

Consult with Paragon for technical literature and to obtain samples

Product Reference: - PARAGON Workspace Solid

TYPE: Tufted loop pile tile

BS 1307 Classification

Category: N

LEVEL OF USE: 4

Size 500 x 500mm

8 colours available

Method of laying: BS5325 Loose Lay after acclimatization for 24 hours. For underfloor
heating application, heater must be turned off for a minimum of 48 hours prior to laying
and after laying brought up to operating temperature in flow increments, over a 48 hours
period.

Adhesive: - F. Ball's, F41 or Similar .

Warranties. 10 Year Bitumen Tile